

800.390.2301 Phone or Fax

www.LBKSkylight.com

::AUSTIN:: 512.320.9972 ::OKC:: 405.445.3487

::CORPORATE OFFICE | 701 N Interstate 27 | Lubbock, TX 79403 | 806.744.2300::

"Manufacturing								
Curb Mount Insulated Glass Insulated Curb	Curb Mount Single Domed Custom Curb							
CMGGIC	CMSDCC							
0.062" Aluminum 0.250" LoE Coated								
Retaining Rail Tempered Laminated	Acrylic (Polycarbonate) Domed (Pyramid)							
Outboard Lite Air Space Inboard Lite								
Butyl								
Sealant	Fastener							
	Condensation Fastener (by others)							
4 5/8" Sealant (By Others)	Gutter							
	0.062" Extruded Aluminum Frame							
Wood Nailer (By Others)	Quarter Quart							
Flashing 💛 🍎	Custom Curb							
Clearance	(By Others)							
Insulation (By Others)								
Roofing Anchor /								
Sealant \	/ Flashing							
(By Others) Rough Opening Mea	/ 9							
(Only Needed if We're Making Cu								
Inside Frame Measurements (If w	ve are not making curbs)							
WE DO NOT RECOMMEND SINGLE DOMES EXCEPT IN SPECIAL CIRCUMSTANCES								
WE DO NOT RECOmmend Small Domes Exact The St Colar Circumstances								

SPECIFICATIONS:: Curb Mount Skylights with glass glazing shall be manufactured by LBK Skylight Manufacturing [(800) 390-2301]. Each skylight shall be factory assembled with insulated glass glazing or acrylic (polycarbonate). Glass will have a 0.250" LoE coated, tempered outboard lite, 0.500" air space and 0.177 / 0.030 PVB 0.177" laminated inboard lite. Overall thickness of glass shall be 1.154". Glass will be clear, bronze or gray. Laminate is available in clear or white, but generally estimated as clear. Acrylic options:: Standard duty (0.118" over 0.118"), Commercial duty (0.187" over 0.118") or Fall protection (0.177" 100% DR Impact Modified Acrylic over 0.177" Acrylic) in either 2412 bronze over clear or 2447 white over clear. Frames shall be .062"extruded aluminum (6063-T5) with welded corners and an integral condensation gutter. Finish shall be mill / natural aluminum or color. Skylight is designed and manufactured to meet or exceed standard of 40 psf live load and 20psf (uplift). Available with or without curbs. Some sizes may have color and/or material limitations. Estimated with integrated support system. Also estimated as commercial duty acrylic over acrylic (0.187" over 0.118") in either 2412 bronze over clear or 2447 white over clear.

ALL UNITS ARE GUARANTEED AGAINST DEFECTIVE WORKMANSHIP AND MATERIAL.

**INSULATED GLASS COLOR** 

Dоме	Dome Material					Dome Color			Dome Type	
ORDER	ACRYLIC	COMMERCIAL DUTY		FALL PROTECTION	WHITE	BRONZE	CLEAR	DOMED	PYRAMID	
OUTER										
INNER										
THIRD										
SKYLIGHT FRAME FINISH			CURB OPTIONS	QTY	INSIDE FRAME		Daview Opposite			
☐ NATURAL ALUMINUM (MILL)		□ No			MEASUREMENT		ROUGH OPENING			
☐ BRONZE PAINT		☐ SEA	☐ SEAL SKYLIGHT TO CURB							
☐ CUSTOM COLOR		□ Na <sup>·</sup>	☐ NATURAL ALUMINUM (MILL)							
			☐ Cus	STOM COLOR						
CURB HEIGHT		☐ Inst	☐ INSULATED							
□ 6"	□ 12	2"	□ Nor	N-INSULATED		•	•			
□ 9"										

IF WE ARE MAKING THE CURBS--WE NEED THE ROUGH OPENING MEASUREMENT. IF YOU ARE MAKING THE CURBS OR USING EXISTING CURBS--WE NEED THE INSIDE FRAME MEASUREMENT THAT IS BIG ENOUGH TO FIT OVER YOUR CURB, FLASHING, ROOF WORK PLUS 1/2" FLASHING CLEARANCE.

PROJECT NAME	PO/JOB#	LEAD TIME	TODAY'S DATE	
PROJECT DELIVERY ADDRESS	CITY / STATE / ZIP	SITE CONTACT / PHONE		
REQUESTED BY	PHONE	COMPANY		
ADDRESS	CITY / STATE / ZIP	APPROVAL SIGNATURE		